



HIKVISION
accessories

Ip of surface video intercom

DS-KV9503-WBE1

POWER CONSUMPTION

Power mode	DC
Voltage	12V
Consumption (w)	6W
Amperage	1500mA
PoE power	Yes
Type PoE	PoE 802.3af

INPUTS/OUTPUTS

Alarm input	4
RS485	1
Door sensor	2
Exit button	2
Blocking entry	2
RJ45	1 x 10 / 100

NETWORK CHARACTERISTICS (INTERCOM MONITORS)

Bluetooth	Yes, 2.0
Network protocol	TCP / IP
Memory slot	SD up to 128Gb
IP connection	10 / 100Mbps autoadaptive
Wi-Fi	Si
Tipo de Wi-Fi	IEEE802.11 b / g / n

CAPACITY

Cards	100000
Register	20000
Faces	10000
Extensiones interiores vinculadas	500
Número máximo de sub módulos	16

SYSTEM (RECORDERS)

Processor	Embedded Processor
Operating system	Embedded LINUX
RAM	1024 MB
ROM	4096 MB

GENERAL CHARACTERISTICS (VIDEO INTERCOM)

CAMERA

Resolution	2 x 2 Mpx
Horizontal viewing angle	88°
Diagonal angle of view	44°
Night vision	Yes, up to 3 m
Day / Night	IR
Video compression	H.264

AMBIENT

Operating temperature	-40 °C ~ 60 °C
Degree of protection	IP65
Anti vandal	IK08
Use	Outdoor
Maximum humidity	90%

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	182 x 85 x 26 mm
Net weight	410 g
Weight with packaging	660 g

IDENTIFICATION

Mode	QR code / Keypad / Card / Facial recognition / Bluetooth
Type of card	MIFARE 13.56MHZ
Face recognition distance	0.3 m – 2.0 m
Face recognition speed	< 0.2 s

GENERAL INFORMATION

Serie	PVPH
Technology	IP
Number of homes	1

AUDIO (VIDEO INTERCOM)

Sound input	Omni-directional microphone
Sound output	Built-in speaker

