


**HIKVISION**  
intrusion

## Wireless volumetric detector

**DS-PDP15P-EG2-WE**

### DETECTION

Detector type	<b>Wireless</b>
Detection distance	<b>15 m</b>
Angle detection	<b>90°</b>
Installation height	<b>2 m ~ 4 m</b>
Detection speed	<b>0,3 m/s ~ 2 m/s</b>
Detection zones	<b>84</b>
Pets immunity	<b>Up to 30 Kg</b>
PIR detection advance at ground level (PIR Creep)	<b>Sí</b>

### POWER CONSUMPTION

Power mode	<b>Battery</b>
Built in battery	<b>Yes</b>
Battery model	<b>CR123A / 3V</b>
Battery duration	<b>Up to 5 años</b>

### ESPECIFICACIONES TÉCNICAS

Compatibility	<b>Hikvision panels</b>
LED indicators	<b>Sí</b>
LED colors	<b>Blue</b>
Tamper	<b>Sí</b>

### VIA RADIO

Frequency	<b>868mHz</b>
Transmission distance	<b>Up to 1600 m (without obstacles)</b>

### GENERAL INFORMATION

Serie	<b>AXPRO</b>
-------	--------------

### MATERIAL AND DIMENSIONS

Installation	<b>Wall / ceiling</b>
Dimensions	<b>103 x 65.5 x 48.5 mm</b>
Net weight	<b>100 g</b>
Weight with packaging	<b>170 g</b>

### AMBIENT

Operating temperature	<b>-10 °C ~ 55 °C</b>
Use	<b>Indoor</b>
Maximum humidity	<b>90%</b>

### SENSOR

Type of sensor	<b>PIR</b>
Sensitivity adjustment	<b>Sí</b>
Digital temperature compensation	<b>Sí</b>

### CERTIFICATION

Grade	<b>2</b>
Environmental class	<b>II</b>