



HIKVISION
intrusion

Wired volumetric double technology detector

DS-PDD15AM-EG2

DETECTION

Detector type	Wired
Detection distance	15 m
Angle detection	85.9°
Installation height	1.8 m ~ 2.4 m
Detection speed	0,3 m/s ~ 2 m/s
Detection zones	52
Antimasking	Sí
Anti-cloaking technology (activation of alarm after infrared detection AND / OR microwave)	Sí
PIR detection advance at ground level (PIR Creep)	Sí
IFT technology	Sí

SENSOR

Type of sensor	PIR and microwave
Sensitivity adjustment	Sí
Microwave	24GHz
Digital temperature compensation	Sí

AMBIENT

Operating temperature	-10 °C ~ 55 °C
Use	Indoor
Maximum humidity	90%

CERTIFICATION

Grade	2
Environmental class	II

ESPECIFICACIONES TÉCNICAS

Compatibility	Hikvision panels
LED indicators	Sí
LED colors	Azul / Verde / Rojo
Tamper	Sí

POWER CONSUMPTION

Power mode	DC
Voltage	9V ~ 16V
Amperage	25mA

MATERIAL AND DIMENSIONS

Dimensions	103.8 x 65.7 x 45.5 mm
Net weight	100 g
Weight with packaging	160 g

GENERAL INFORMATION

Serie	AXPRO
-------	--------------

