



HIKVISION
accessories

Access control and indoor /
outdoor video intercom with QR
code, keypad and card

DS-K1T502DBWX-CQR

INPUTS/OUTPUTS

Alarm input	1
RS485	1
Door sensor	1
Exit button	1
Blocking entry	1
Alarm output	1

POWER CONSUMPTION

Power mode	DC
Voltage	12V ~ 24V
Consumption (w)	12W
Amperage	1000mA

MATERIAL AND DIMENSIONS

Installation	Surface
Dimensions	177 x 81 x 26.1 mm
Net weight	620 g
Weight with packaging	1030 g

COMMUNICATION

Wi-Fi	Sí
Bluetooth	Yes
Mode	Wiegand / RS485

FUNCTIONS OF SYSTEM (CONTROLS PRESENCE / ACCESS)

SD card	Up to 256 GB
---------	--------------

AMBIENT

Operating temperature	-40 °C ~ 70 °C
Degree of protection	IP65
Anti vandal	IK09
Use	Indoor-outdoor

FEATURES

Integrated controller	Sí
Tamper	Sí
Camera	2 Mpx
Integrated microphone	Yes

IDENTIFICATION

Mode	QR code / Keypad / Card
Type of card	MIFARE / DESFIRE 13.56MHz

GENERAL INFORMATION

Control type	Control de acceso y videoportero
--------------	----------------------------------

