



Wired module with 4 inputs  
and 4 outputs

## MULTITRANSMITTER-FIBRA- IO4X4



### POWER CONSUMPTION

|              |            |
|--------------|------------|
| Power mode   | DC         |
| Voltage      | 12V ~ 28V  |
| Amperage     | 330mA      |
| Power output | 3 x DC 12V |

### TECHNICAL SPECIFICATIONS

|                             |                             |
|-----------------------------|-----------------------------|
| LED indicators              | Yes                         |
| EOL resistors (end of line) | Si                          |
| Connection type             | NC / NO / EOL / 2EOL / 3EOL |
| Transmission distance       | Up to 2000 m                |

### MATERIAL AND DIMENSIONS

|                       |                 |
|-----------------------|-----------------|
| Dimensions            | 93 x 55 x 27 mm |
| Net weight            | 45 g            |
| Weight with packaging | 80 g            |

### INPUTS/OUTPUTS

|                   |                         |
|-------------------|-------------------------|
| Number of entries | 4                       |
| Number of exits   | 4 (2 logical / 2 relay) |

### AMBIENT

|                       |                |
|-----------------------|----------------|
| Operating temperature | -10 °C ~ 40 °C |
| Use                   | Indoor         |
| Maximum humidity      | 75%            |

### CERTIFICATION

|                     |         |
|---------------------|---------|
| Grade               | 3       |
| Normative           | EN50131 |
| Environmental class | II      |

### SABOTAGE

|            |    |
|------------|----|
| Box tamper | Si |
|------------|----|

